

P R O F E S S I O N A L L I N E

BIOFA



WOHNGESUND & NACHHALTIG

PRODUCTS FOR
INDUSTRIAL AND PROFESSIONAL
PROCESSING



BIOFA - so that your home becomes an oasis of well-being.

Healthy living, sustainability, best quality and experience since 1976, that's what BIOFA - your expert in oils - offers.

Since its foundation, BIOFA has attached great importance to a holistic approach to quality. This means that BIOFA closely monitors and checks the quality and safety of its products, from the origin of the raw materials or ingredients, through



production, to the finished product and the subsequent recycling process. The trust and high expectations of consumers in TOP BIOFA quality is also confirmed by renowned quality seals. This is because all BIOFA products are subject to strict test criteria that generally go far beyond the regulations of the legislator. The quality of the products and also the raw materials are tested by independent institutes using the most modern testing methods. This ensures national and international standards.

Areas of application

Floors:

8630, 86301 Profi Top Oil solvent-free: primer and finishing coat for machine and manual application.

silk-glossy, colourless and transparent coloured, fulfils the parquet standard DIN EN 14342 (DIBt) and the toy standard EN 71

8624, 86241 Profi Top Oil: Primer and top coat for spraying and for machine and manual application

silk gloss, colourless and transparent coloured, meets parquet standard DIN EN 14342 (DIBt)

8683 Bianco Oil: Primer and finishing coat for machine and manual application matt, transparent white, the wood looks like untreated, fulfils the parquet standard DIN EN 14342 (DIBt)

8689 Bianco Oil Aqua: Primer and finishing coat for machine and manual application matt, transparent white, water-dilutable, the wood looks like untreated, fulfils the toy standard EN 71,3 and the standard for sweat and saliva fastness DIN 53 160

Furniture:

8662 Dipping oil solvent-free: primer and finishing coat for dipping. silk matt, colourless, complies with toy standard EN 71

8624, 86241 Profi Top Öl: Primer and top coat for spraying and for machine and manual application silk gloss, colourless and transparent coloured, meets parquet standard DIN EN 14342 (DIBt)

8660 Spray Oil Wax solvent-free: primer and top coat for cold or warm, machine and manual application silk matt, colourless

8683 Bianco Oil: Primer and finishing coat for machine and manual application matt, transparent white, the wood looks like untreated, fulfils the parquet standard DIN EN 14342 (DIBt)

8689 Bianco Oil Aqua: Primer and finishing coat for machine and manual application matt, transparent white, water-dilutable, the wood looks like untreated, fulfils the toy standard EN 71,3 and the standard for sweat and saliva fastness DIN 53 160

Interior finishing:

8630, 86301 Profi Top Oil solvent-free: primer and finishing coat for machine and manual application.

silk-glossy, colourless and transparent coloured, fulfils the parquet standard DIN EN 14342 (DIBt) and the toy standard EN 71

8045, 8245 Hard Oil Aqua: Primer and finishing coat for spraying and manual application

silk-matt and matt, colourless, largely non-yellowing, water-dilutable, complies with toy standard EN 71

8162 Hard Wax Oil: Primer and finishing coat for manual application matt, colourless, largely non-yellowing

8624, 86241 Profi Top Oil: Primer and top coat for spraying and for machine and manual application silk gloss, colourless and transparent coloured, meets parquet standard DIN EN 14342 (DIBt)

8683 Bianco Oil: Primer and finishing coat for machine and manual application matt, transparent white, the wood looks like untreated, fulfils the parquet standard DIN EN 14342 (DIBt)

8689 Bianco Oil Aqua: Primer and finishing coat for machine and manual application matt, transparent white, water-dilutable, the wood looks like untreated, fulfils the toy standard EN 71,3 and the standard for sweat and saliva fastness DIN 53 160

Toys:

8662 Dipping oil solvent-free: primer and finishing coat for dipping. silk matt, colourless, complies with toy standard EN 71

8630, 86301 Profi Top Oil solvent-free: primer and finishing coat for machine and manual application. silk-glossy, colourless and transparent coloured, fulfils the parquet standard DIN EN 14342 (DIBt) and the toy standard EN 71



8689 Bianco Oil Aqua: Primer and finishing coat for machine and manual application matt, transparent white, water-dilutable, the wood looks like untreated, fulfils the toy standard EN 71,3 and the standard for sweat and saliva fastness DIN 53 160



Hard Oil Aqua silk matt 8045, matt 8245

For the rational and time-saving, manual priming and finishing of absorbent wooden floors, wood-based panels, interior fittings and exterior furniture surfaces in interior areas.


BIOFA Hard Oil Aqua is a water-thinnable coating. It revives the natural structure of the treated substrates and produces a hard-wearing and water-repellent surface that is largely non-yellowing. It complies with the toy standard EN 71. GS values: rubber smooth GS 2, rubber fine grooved GS 3, plastic coarse grooved GS 3, leather smooth GS1
EU limit value (cat. A/i): 140 g/l (2010), 8045, 8245 contains max. 1.3 g/l VOC.



Hard Wax Oil matt 8162

For the rational and time-saving manual priming and finishing of absorbent wood, wood-based panels such as sterling OSB panels, etc. indoors.


BIOFA Hard Wax Oil matt is a high-quality product made from natural raw materials. It revives the natural structure, deepens the tint of the treated substrates and results in an open-pored, silk-matt, hard-wearing and water-repellent surface that is largely non-yellowing.
EU limit value (cat. A/i): 500 g/l (2010), 8162 contains max. 450 g/l VOC.



Profi Top Oil colourless 8624, coloured 86241

For mechanical (application by roller or spraying) and manual priming and finishing of absorbent wood floors, wood-based panels such as sterling OSB panels, etc., interior finishing and exterior furniture surfaces.


BIOFA Profi Top Oil is a high-quality product made from natural raw materials on the basis of an oil-resin boiling process. It refines the wood permanently and results in a resistant, diffusion-open and antistatic surface. The natural wood character is deepened and the surface is given a velvety sheen. It meets the parquet standard DIN EN 14342 (DIBt)
EU limit value (cat. A/f): 700 g/l (2010), 8624, 86241 contains max. 240 g/l VOC.



Profi Top Oil solvent-free colourless 8630, coloured 86301

For machine (roller application) and manual priming and finishing of absorbent wood floors, wood-based panels such as sterling OSB panels, etc., interior finishing, exterior furniture surfaces and wooden toys.

BIOFA Profi Top Oil solvent-free is a high-quality natural product made of an oil-resin boiling and waxes. It refines the wood permanently and results in resistant and diffusible surfaces. Due to its good penetration capacity and its oily character, it revives the natural structure of the wood and gives it a velvety sheen.
EU limit value (cat. A/f): 700 g/l (2010), 8630, 86301 contains max. 1 g/l VOC.



BIOFA
SOLVENT-FREE




Spray Oil Wax solvent-free 8660

For cold and hot machine (roller or spray application) and manual priming and finishing of absorbent wooden furniture. wooden furniture.

BIOFA Spray Oil Wax Solvent Free is a colourless oil made from high-quality, natural raw materials. It penetrates very well, revives and deepens the natural structure and shade of the treated wood and results in a resistant, diffusible and antistatic surface. 8660 contains max. 1 g/l VOC.

BIOFA
SOLVENT-
FREE




Dipping oil solvent-free 8662

Primer and finishing coat for absorbent woods, furniture surfaces and toys. For application by dipping.

BIOFA Dipping Oil solvent-free is a colourless oil made from high-quality, natural raw materials. It penetrates well, revives and deepens the natural structure and shade of the treated wood and results in a resistant, diffusible and antistatic surface. It complies with the EN 71 toy standard. 8662 contains max. 3 g/l VOC.

BIOFA
SOLVENT-
FREE




Bianco Oil 8683

For machine (processing by rolling) and manual priming and finishing of absorbent wood floors, wood-based panels such as sterling OSB panels, etc., interior finishing and exterior furniture surfaces.

BIOFA Bianco Oil is a high-quality wood coating and produces a matt, open-pored, hard-wearing, dirt- and water-repellent surface. The natural colour of the wood remains largely unchanged after treatment. There is hardly any kindling and the natural yellowing is delayed.

EU limit value (cat. A/i): 500 g/l (2010), 8683 contains max. 490 g/l VOC.




Bianco Oil Aqua 8689

For machine (processing by rolling) and manual priming and finishing of absorbent wood floors, wood-based panels such as sterling OSB panels, etc., interior finishing and exterior furniture surfaces.

BIOFA Bianco Oil is a high-quality wood coating and produces a matt, open-pored, hard-wearing, dirt- and water-repellent surface. The natural colour of the wood remains largely unchanged after treatment. There is hardly any kindling and the natural yellowing is delayed.

EU limit value (cat. A/i): 500 g/l (2010), 8689 contains max. 50 g/l VOC.



BIOFA
WOHNGESUND & NACHHALTIG

BIOFA Naturprodukte W. Hahn GmbH
Dobelstr. 22 • D-73087 Bad Boll • T: +49 7164 / 9405 0 •
F: +49 7164 / 9405 96 • info@biofa.de • www.biofa-de.com