

BIOFA 
WOHNGESUND & NACHHALTIG



Worktop Oil 2052

solvent-free, for indoor use

- fully declared
- made of 97% renewable and mineral raw materials
- successfully tested for healthy indoor air
- certified: Food-safe, toy standard, sweat and saliva-safe





Oil from nature ...

The solvent-free BIOFA Worktop Oil was developed for the basic treatment and care of worktops and tables in interior areas. It is low-emission and consists of 97% renewable and mineral raw materials, which offer a wide range of benefits. The natural oils ensure a resistant, dirt and water-repellent surface and adapt flexibly to the needs of the wood. This unique, silky-glossy, natural-looking and elegant wood surface is the result of an optimised composition of natural raw materials. The Worktop Oil fulfils the standards EC 1935/2004 food compatibility, DIN 53160 sweat and saliva fastness, DIN EN 71.3 toy standard and is listed with Sentinel Haus QNG-Ready (fulfils the requirements for KfW funding).





Worktop Oil




BIOFA Worktop Oil solvent-free

- fully declared
- low emission
- made of 97% renewable and mineral raw materials
- colourless and silky gloss
- breathable and antistatic
- dirt and water repellent
- sweat and saliva resistant
- food-safe and stain-resistant
- partially repairable



Anyone wishing to receive funding for a new home from the KfW development bank must fulfil sustainability criteria. These are confirmed by the Quality Seal for Sustainable buildings, QNG for short.





Application::





Primer, finishing coat and maintenance for tables, worktops and toys.

Untreated surfaces: The surface must be dry and clean. Final sanding with P180-200. Stir worktop oil thoroughly and apply evenly with a brush, lint-free cloth or by spraying. After 20-30 minutes penetration time, expel or absorb any excess oil from areas that are still absorbent. Pad in thoroughly with a green pad and polish dry with a white pad. Repeat the process the next day, but only pad in and polish out with a white pad.

For the care of solvent-free oiled surfaces: Stir worktop oil thoroughly and apply thinly and evenly. After a penetration time of 15 to 30 minutes, remove or absorb any excess oil from areas that are still absorbent. Pad in thoroughly with a white pad and polish dry.

Cleaning: For cleaning we recommend the pH-neutral concentrate BIOFA NACASA Universal Cleaner 4010 or the ready-to-use BIOFA Household Cleaner Spray 4020, which is also pH-neutral.

Maintenance care: For the regular maintenance care we recommend the concentrate BIOFA NAPLANA Care Emulsion 2085 or the ready-to-use BIOFA Wax Care Spray 4030.



Your local retailer:

BIOFA Naturprodukte W. Hahn GmbH
Dobelstr. 22 ♦ D-73087 Bad Boll
T: +49 7164 / 9405 0 ♦ F: +49 7164 / 9405 96
info@biofa.de ♦ www.biofa-de.com

