

BIOFA 
WOHNGESUND & NACHHALTIG



Worktop Oil 2052

solvent-free, for indoor use

- fully declared
- made of 97% renewable and mineral raw materials
- successfully tested for healthy indoor air
- certified: Food-safe, toy standard, sweat and saliva-safe





Oil from nature ...

The solvent-free BIOFA Worktop Oil was developed for the basic treatment and care of worktops and tables in interior areas. It is low-emission and consists of 97% renewable and mineral raw materials, which offer a wide range of benefits. The natural oils ensure a resistant, dirt and water-repellent surface and adapt flexibly to the needs of the wood. This unique, silky-glossy, natural-looking and elegant wood surface is the result of an optimised composition of natural raw materials. The Worktop Oil fulfils the standards EC 1935/2004 food compatibility, DIN 53160 sweat and saliva fastness, DIN EN 71.3 toy standard and is listed with Sentinel Haus QNG-Ready (fulfils the requirements for KfW funding).





Worktop Oil



BIOFA Worktop Oil solvent-free

- fully declared
- low emission
- made of 97% renewable and mineral raw materials
- colourless and silky gloss
- breathable and antistatic
- dirt and water repellent
- sweat and saliva resistant
- food-safe and stain-resistant
- partially repairable



Anyone wishing to receive funding for a new home from the KfW development bank must fulfil sustainability criteria. These are confirmed by the Quality Seal for Sustainable buildings, QNG for short.





SHI product passport:

Healthy living – Find products – Certify buildings

All relevant product qualities regarding health compatibility and environmental impact of the product, which are required to achieve sustainable building certifications, can be found in the SHI product passport.

This QR code will take you to the SHI product passport for BIOFA Worktop Oil 2052.



Application::





Primer, finishing coat and maintenance for tables, worktops and toys.

Untreated surfaces: The surface must be dry and clean. Final sanding with P150-180. Stir worktop oil thoroughly and apply evenly with a brush, lint-free cloth or by spraying. After 20-30 minutes penetration time, expel or absorb any excess oil from areas that are still absorbent. Pad in thoroughly with a green pad and polish dry with a white pad. Repeat the process the next day, but only pad in and polish out with a white pad.

For the care of solvent-free oiled surfaces: Stir worktop oil thoroughly and apply thinly and evenly. After a penetration time of 15 to 30 minutes, remove or absorb any excess oil from areas that are still absorbent. Pad in thoroughly with a white pad and polish dry.

Cleaning: For cleaning we recommend the pH-neutral concentrate BIOFA NACASA Universal Cleaner 4010 or the ready-to-use BIOFA Household Cleaner Spray 4020, which is also pH-neutral.

Maintenance care: For the regular maintenance care we recommend the concentrate BIOFA NAPLANA Care Emulsion 2085 or the ready-to-use BIOFA Wax Care Spray 4030.



Your local retailer:

BIOFA Naturprodukte W. Hahn GmbH
Dobelstr. 22 ♦ D-73087 Bad Boll
T: +49 7164 / 9405 0 ♦ F: +49 7164 / 9405 96
info@biofa.de ♦ www.biofa-de.com

